

# RY | 280 STANDARD SPECIFICATION



## technical details according to ISO 8666

LOA incl. anchor arm	9.16 m	30' 1"	Air draft max	2.44 m	8' 0"
LOA incl. anchor arm + engine	9.51 m	31' 2"	Water tank	88 l	19 UK gal
Hull length	8.80 m	28' 10"	Fuel tank	300 l	66 UK gal
Beam	2.81 m	9' 3"	Displacement	2.07 t	2.04 UK t
Draft excl. engine	0.53 m	1' 9"	CE Category	C	C
Draft incl. engine	0.91 m	2' 12"	Max. persons	8	8

\*Max. outboard horse power: 1x350 hp; max. speed allowed: 45 knots. RY reserves the right to change specifications in line with the company policy of improvement through research and development. All measurements/figures approximate. Errors and omissions are excepted. Specification and material can be changed without notice. Please check with your dealer for a full list of inclusions. Valid from 2021.07.01.

# RY | 280 EXTERIOR/INTERIOR LAYOUT



**STANDARD**  
Fiberglass deck



**OPTION**  
Table, wetbar,  
bench & bow  
upholstery



**OPTION**  
Back rest  
lower & raise,  
wetbar



**OPTION**  
T-top



**STANDARD**  
Storage & Head



**OPTION**  
Cabin & Head

EXTERIOR ▶

INTERIOR ▶

INSTANTLY THRILLING

RYBOATS.COM



## HULL

- GRP hull, isophthalic gelcoat, colour: light grey (RAL 7047), 1st layer vinyl ester resin

## DECK & COCKPIT

- Dashboard, painted, colour: medium grey (RAL 7016) with satin finish, handrails on dashboard and side to companionway, switch panel backlit
- GRP deck with antislip surface, isophthalic gelcoat, colour: light grey (RAL 7047), 1st layer vinyl ester resin. Self draining anchor locker. Raised deckhouse at bow.
- Gunwale in GRP
- Fender strip, rubber, colour: black
- RY steering wheel with logo
- 2 skylights (on the side), 1 openable hatch on raised deck and 1 openable hatch in toilet
- Plexiglass door to companionway with lock cylinder
- Full clear windscreen with wiper
- Emergency ladder
- 6 stainless steel cleats (aft, midship, forward), side handrails
- Pilot and copilot seats - Exciting Outdoor, colour: dim grey (according to colour card)
- L-shaped cockpit bench in fiberglass and big storage area under the cockpit with manual

opening

## PROPULSION

- Engine battery preparation incl. main switches
- Fuel tank, capacity: 300 litres

## ELECTRICAL EQUIPMENT

- 12 V electric system with main switchboard. Sockets 12 V on dashboard (2) and bow storage
- Batteries-Service: 1 x 90 Ah AGM
- Country Version: EU / AUS
- Toilet, manual
- Spotlights in bow storage and toilet
- Holding tank black water, capacity: 35 litres
- Freshwater system with electric pump
- Freshwater tank, capacity: 88 l
- Bilge pumps: automatic electric (1) and manual emergency bilge pump in cockpit (1)

## NAVIGATION & INSTRUMENTS

- Navigation lights - LED

## LAYOUT & INTERIOR

- A1: Storage with 1 spotlight and fully equipped head with sea water flush toilet

## UPHOLSTERY & WOOD

- Interior bulkhead in layout A1 in Shift Ecru Oak, flooring in bow storage and toilet in GRP with antislip, gelcoat colour: white

## TRANSPORT

- Identified locations for hand held fire extinguishers - (hand held fire extinguishers are not supplied), RY Owner's Manual in RY document bag